

# High precision - hardened casing - Designed to last

The Abeeway Compact Tracker is a highly versatile multi-mode tracker with embedded sensors combining GPS, Low-power GPS, Wi-Fi Sniffer, BLE and LoRaWAN™ TDoA geolocation technologies, supporting accurate outdoor & indoor geolocation.

Best of all, it has a **compact and robust form factor**, designed to resist **harsh surroundings** enabling you to perform seamless asset tracking, **proximity detection** and management in any industrial environment – whether it's for **heavy-duty assets or small equipment**, taking advantage of its **long battery autonomy**.

# **Applications:**

- Real-time tracking, status monitoring of heavy and light assets, vehicles, machines and equipment, outdoors or in indoor industrial facilities.
- Activity monitoring based on motion for usage optimization, industrial control and asset management
- Livestock tracking in large farms
- Optimization of supply chain and production, delivery and inventory tracking
- Geofencing applications: receiving zone alerts when leaving/entering specific areas
- Antitheft applications, notification and location trigger when device is moving, at fixed frequency updates or on demand

# **Product Highlights**

#### Multiple operating modes:

- Motion Tracking: Real-time position at a given cycle when motion is detected.
- **Permanent tracking:** Regular interval real time position.
- Start/End motion tracking: Receive position messages during motion start and end events.
- Fix on demand: Obtain tracker position when needed (very low power operating mode)
- Activity tracking: Monitor activity rate with embedded sensors.
- Geozone detection: capability to detect specific zones that matter for your processes.

#### Geolocation technologies:

- **GPS:** Precise outdoor position
- Low power GPS: Fast Time To First Fix in outdoor and daylight indoor conditions
- Wi-Fi & BLE: Position in indoor and urban area

#### Other features:

- Geofencing zone detection
- Proximity detection
- Temperature monitoring
- LoRaWAN® Class A radio
- Waterproof enclosure (IP68); IK08
- Firmware upgrade
- Replaceable AA batteries
- Very modular fixation
- Magnetic switch (optional)
- Pressure sensor (Optional)
- Speaker (optional)
- ATEX certification<sup>(5)(6)</sup>
- BLE scan function for inventory of tools and accessories
- Indoor BLE/WiFi fingerprinting with HERE Tracking (requires subscription)
- Indoor BLE based geolocation with Quuppa Intelligent Location (requires Quuppa infrastructure)
- BLE based safe/hazard zone detection



# Physical configuration

Size	112mm x 66mm x 33mm (L x l x h)
Weight	190g
Waterproof capability and resistance	IP68, IK08
Operating temperatures	-20°C to +65°C
Storage temperature	10°C to 30°C (recommended)
Time storage max	12 months
Humidity	< 95% non-condensing

### **Estimated lifetime**

Use Case	Battery Life (Approx.)	
1 GPS fix per hour (2)	1 year	
1 LPGPS fix per hour (2)	4 years	
1 WiFi scan per hour	7 years	
1 BLE scan every 3 min	> 5 years	
Standby	> 5 years	

# Data communication support

LoRaWAN™ Modem	Semtech transceiver SX1262
Protocol	LoRaWAN Class A
LoRaWAN™ Frequency bands (1)	EU868MHz / US915MHz / AS923MHz / AU915 MHz
Configuration supported	OTA or ABP
RF output power <sup>(1)</sup>	14 dBm / 19 dBm (max)
LoRaWAN™	-130 dBm in SF10
receiver sensitivity	
WI-FI sniffer sensitivity	-86 dBm
WI-FI frequency band	2412 - 2472MHz
BLE RF output power	3 dBm max
BLE sensitivity	-88 dBm
GNSS band	1575 – 1610MHz

# Standards and Certifications

LoRa Alliance EU868, US915, AS923, IN865, AU915 Radio regulatory certification : EC, FCC, IC, TELEC, IMDA

# **Position accuracy**

GPS <sup>(3)</sup>	Position Accuracy (50%-90%)	10 to 18 meters	10 to 18 meters	
	Time To First Fix	Cold start	30-45 seconds	
		Hot start	<5 seconds	
	Acquisition sensitivity	-140 dBm		
Low power GPS(3)	Position Accuracy (50%-90%)	15 - 30 meters		
	Time To First Fix	< 10 seconds		
	Acquisition sensitivity	-145 dBm		
Wi-Fi <sup>(4)</sup>	Indoor Position Accuracy	20 - 50 meters		
	Time to get a position	3 seconds		
BLE for positioning <sup>(4)</sup>	Indoor Position Accuracy	5 - 15 m		
	Time to get a position	1 second		
BLE for proximity	Proximity Detection accuracy	< 1m	_	

# Power management

Primary battery	3x AA/3.6V (Li-SOCl2) -Nominal of	capacity 8Ah	

## **Product references**

Product	SKU		
ABE COMPACT TRACKER EU868	DEABE510-XXXEU	DEABE512-XXXEU-Ex0 (5)	DEABE514-XXXEU-Ex2 (6)
ABE COMPACT TRACKER IN865	DEABE510-XXXIN	DEABE512-XXXIN-Ex0 (5)	DEABE514-XXXIN-Ex2 (6)
ABE COMPACT TRACKER US915	DEABE511-XXXUS	DEABE513-XXXUS-Ex0 (5)	DEABE515-XXXUS-Ex2 (6)
ABE COMPACT TRACKER AS923	DEABE511-XXXAS	DEABE513-XXXAS-Ex0 (5)	DEABE515-XXXAS-Ex2 (6)
ABE COMPACT TRACKER AU915	DEABE511-XXXAU	DEABE513-XXXAU-Ex0 (5)	DEABE515-XXXAU-Ex2 (6)

- (1) Channel frequencies and Transmit output power level are country specific and controlled by the operator
- (2) Assuming 5 satellites at -130dBm input power
- (3) Assuming 5 satellites at -130 dBm input power
- (4) Accuracy depends on the BLE beacon or WiFi AP density and physical layout of the premises
- (5) ATEX Zone 0: **②** II 1G Ex ia IIC T4 Ga Ta -20 °C ... +40 °C
- ,(6) ATEX Zone 2: ऒ 3G Ex ic nA IIC T4 Gc Ta -20 °C ... +40 °C
  - **⑤** II 3D Ex ic tc IIIB T135°C Dc Ta -20 °C ... +40 °C

Abeeway is the market leader in low-power geolocation and a provider of disruptive IoT tracking solutions worldwide. Abeeway offers the most energyefficient, reliable and flexible geolocation solutions using unique tracking devices and a smart multitechnology location system optimized for longrange and low-power-consumption LoRaWAN® connectivity. Offering the fastest time-to-market, Abeeway delivers a complete end-to-end solution for mass-market IoT sectors for asset tracking and management, process and decision optimization and personal safety. Abeeway is a member of the LoRa Alliance® and part of the Actility Group. Actility Group is a leading provider of LPWA IoT connectivity solutions, tools, business services and applications.